


# BBG-2OE-MK2 Dual Fiber-To-Coax

3G/HD/SD-SDI / ASI / MADI Fiber Optic Dual Transport Receiver

The **BBG-20E-MK2 Dual Fiber-To-Coax** (hereinafter called "BlueBox<sup>™</sup> 2OE") provides a small "throwdown" package that supports SMPTE 424M, 292M, and 259M as well as ASI and MADI audio on two independent fiber-to-coax paths. Auto-mode EQ/reclocking automatically sets to the signal type being received while allowing unrecognized formats to be safely passed without reclocking (auto-reclock can also be manually disabled for either path as desired). Its wide operating range (from 5Mbps to 3Gbps) flexibly supports most professional digital serial communications. Fully error-free pathological pattern operation is fully compatible with other professional fiber video interfaces.

Note: BlueBox<sup>™</sup> 2OE does not support AES-3id transports.

The unit receives its DC power from either connecting its USB port to associated equipment, or by the supplied AC adapter.



## Connecting BlueBox<sup>™</sup> 2OE

- 1 Connect BlueBox<sup>™</sup> 2OE to DC power using the supplied AC adapter.
- 2. Remove any protective caps on fiber cables and/or input receptacles. Connect Fiber input and BNC Coax output to channel 1 and/or channel 2 inputs/outputs. This provides the basic conversion connections. Unused connections do not require termination.



CLASS 1 LASER PRODUCT

IEC 60825-1:2007 Caution - INVISIBLE LASER RADIATION. AVOID EXPOSURE TO THE BEAM.

#### Status Indicator

BlueBox<sup>™</sup> 2OE has **Status** LEDs (one LED for each input channel) on the side of the unit which functions as follows:

- Solid Green Recognized SDI present.
- Green Flash No SDI present, or not recognized as SDI.

#### **Reclocker Auto/Bypass Switches**

BlueBox<sup>™</sup> 2OE DIP switches SW2 and SW3 (for Fiber 1 and Fiber 2 inputs respectively) allow for reclocker Auto-Bypass when recognized SDI is not being received, or Always Bypass reclocking. Refer to illustration on rear label on unit for switch positions.

#### **Configure Select Using DIP Switch Bank**

BlueBox<sup>™</sup> 2OE can be used in a local control mode using DIP switches to configure settings, or via USB remote control. The USB remote also provides optical Rx power meters for Rx confidence assessment. Refer to diagram on unit label for switch positions.

- If using DIP switch control, make certain switch SW1 is set to **ON**. USB remote control is locked out in this mode.
- If using USB remote control, make certain switch SW1 is set to OFF. DIP switch local control is locked out in this mode.

#### **Specifications**

ltem	Description/Specification
Part Number/ Nomenclature	<ul> <li>BBG-2OE-MK2-FC 3G/HD/SD-SDI / ASI / MADI Fiber Optic Dual Transport Receiver (Type FC fiber connectors)</li> <li>BBG-2OE-MK2-ST 3G/HD/SD-SDI / ASI / MADI Fiber Optic Dual Transport Receiver (Type ST fiber connectors)</li> <li>BBG-2OE-MK2-LC 3G/HD/SD-SDI / ASI / MADI Fiber Optic Dual Transport Receiver (Type LC fiber connectors)</li> </ul>
Power:	5-16 VDC, 2.4 W DC Power Connectors USB Mini and coaxial locking connector (for use with supplied Cobalt power adapter)
Standards/Data Rates supported:	SMPTE 424M, 292M, 259M, 344M, 305M, DVB-ASI 5Mbps to 3Gbps pathological pattern operation (does not support AES-3id audio or other standards using data rates < 5Mbps)
Inputs:	<ul> <li>(2) Fiber input. FC, ST, or LC connectors per ordered configuration (see Part Number/Nomenclature above)</li> <li>Wavelength: 1260 to 1620 nm</li> <li>Sensitivity/Input Usable Range: -18 dBm min; -1 dBm max</li> </ul>
Outputs:	(2) 75Ω BNC. Reclocking automatically engaged for recognized signal standards; bypassed for unrecognized standards. Return Loss: >18 dBm up to 270 MHz
Dimensions (WxHxD):	5.5" x 3" x 1" (including connector projections) (139 x 77 x 26 mm)
Operating Temperature Range	32°F to 122°F (0°C to 50°C)

#### Warranty and Service Information

#### **Cobalt Digital Inc. Limited Warranty**

This product is warranted to be free from defects in material and workmanship for a period of five (5) years from the date of shipment to the original purchaser, except that 4000, 5000, 6000, 8000 and Blue Box series power supplies, and Dolby<sup>®</sup> modules (where applicable) are warranted to be free from defects in material and workmanship for a period of one (1) year.

Cobalt Digital Inc.'s ("Cobalt") sole obligation under this warranty shall be limited to, at its option, (i) the repair or (ii) replacement of the product, and the determination of whether a defect is covered under this limited warranty shall be made at the sole discretion of Cobalt.

This limited warranty applies only to the original end-purchaser of the product, and is not assignable or transferrable therefrom. This warranty is limited to defects in material and workmanship, and shall not apply to acts of God, accidents, or negligence on behalf of the purchaser, and shall be voided upon the misuse, abuse, alteration, or modification of the product. Only Cobalt authorized factory representatives are authorized to make repairs to the product, and any unauthorized attempt to repair this product shall immediately void the warranty. Please contact Cobalt Technical Support for more information.

To facilitate the resolution of warranty related issues, Cobalt recommends registering the product by completing and returning a product registration form. In the event of a warrantable defect, the purchaser shall notify Cobalt with a description of the problem, and Cobalt shall provide the purchaser with a Return Material Authorization ("RMA"). For return, defective products should be double boxed, and sufficiently protected, in the original packaging, or equivalent, and shipped to the Cobalt Factory Service Center, postage prepaid and insured for the purchase price. The purchaser should include the RMA number, description of the problem encountered, date purchased, name of dealer purchased from, and serial number with the shipment.

Cobalt Digital Inc. Factory Service Center2506 Galen DriveOffice: (217) 344-1243Champaign, IL 61821 USAFax: (217) 344-1245www.cobaltdigital.comEmail: info@cobaltdigital.com

THIS LIMITED WARRANTY IS EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND OF ALL OTHER OBLIGATIONS OR LIABILITIES ON COBALT'S PART. ANY SOFTWARE PROVIDED WITH, OR FOR USE WITH, THE PRODUCT IS PROVIDED "AS IS." THE BUYER OF THE PRODUCT ACKNOWLEDGES THAT NO OTHER REPRESENTATIONS WERE MADE OR RELIED UPON WITH RESPECT TO THE QUALITY AND FUNCTION OF THE GOODS HEREIN SOLD. COBALT PRODUCTS ARE NOT AUTHORIZED FOR USE IN LIFE SUPPORT APPLICATIONS.

COBALT'S LIABILITY, WHETHER IN CONTRACT, TORT, WARRANTY, OR OTHERWISE, IS LIMITED TO THE REPAIR OR REPLACEMENT, AT ITS OPTION, OF ANY DEFECTIVE PRODUCT, AND SHALL IN NO EVENT INCLUDE SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS), EVEN IF IT HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

©Copyright 2019, Cobalt Digital Inc. All Rights Reserved.

Duplication or distribution of this manual and any information contained within is strictly prohibited without the express written permission of Cobalt Digital Inc. This manual and any information contained within, may not be reproduced, distributed, or transmitted in any form, or by any means, for any purpose, without the express written permission of Cobalt Digital Inc. Reproduction or reverse engineering of software used in this device is prohibited.

The information in this document has been carefully examined and is believed to be entirely reliable. However, no responsibility is assumed for inaccuracies. Furthermore, Cobalt Digital Inc. reserves the right to make changes to any products herein to improve readability, function, or design. Cobalt Digital Inc. does not assume any liability arising out of the application or use of any product or circuit described herein.

Cobalt<sup>®</sup> is a registered trademark of Cobalt Digital Inc. BlueBox<sup>™</sup> is a trademark of Cobalt Digital Inc.



## **Cobalt Digital Inc.**

2506 Galen Drive Champaign, IL 61821 Voice 217.344.1243 • Fax 217.344.1245 www.cobaltdigital.com

BBG-2OE-MK2-OM (V1.0)

© 2019 Cobalt Digital Inc. All Rights Reserved